

PATENT ABSTRACTS OF JAPAN


(11)Publication number : 2001-044044  
(43)Date of publication of application : 16.02.2001

(51)Int.Cl. H01F 27/06  
H01F 27/28  
H01F 37/00  
H01F 41/10  
// H01B 7/02

(21)Application number : 11-241984 (71)Applicant : CONCORDE DENSHI KOGYO:KK  
(22)Date of filing : 26.07.1999 (72)Inventor : SHIBAZAKI HIROSHI

(54) SURFACE-MOUNTING INDUCTOR

(57)Abstract:  
PROBLEM TO BE SOLVED: To reduce the number of manufacturing steps and improve reliability by easily forming a closed magnetic loop type coil having a large current capacity, eliminating the complicated sealing work due to the resin injection, and simplifying a case molding process without the use of a lead terminal embedding case and also eliminating the process to connect a coil terminal to a lead terminal of the case using solder.  
SOLUTION: A closed magnetic path core is formed by embedding a coil that is formed by winding an insulator-covered flat angular wire around the recessed portions of a couple of magnetic cores, formed of a ferrite material with inclusion of an annular recessed portion at the center and a terminal guiding groove 6 at the side wall. Next, the insulator cover of coil terminal portion is removed and is soldered. Thereafter, a substrate mounting terminal 9 is formed, by continuously folding the wire at the bottom surface of the external circumference portion and two side surfaces.



LEGAL STATUS

[Date of request for examination]  
[Date of sending the examiner's decision of rejection]  
[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]  
[Date of final disposal for application]  
[Patent number]  
[Date of registration]  
[Number of appeal against examiner's decision of rejection]  
[Date of requesting appeal against examiner's decision of rejection]  
[Date of extinction of right]